



INTERCLEAN 150 AB

DESCRIPTION	Ready to use antibacterial water rinsible, non-crazing cleaner. INTERCLEAN 150 AB has been formulated for application on non-porous synthetic materials, polycarbonate, (un) painted substrates, aluminium and fabrics. Effective for "long-lasting clean".	
SPECIFICATION	European Disinfection Test EN 13697: 2015 <i>Antimicrobial Activity against Staphylococcus aureus, Escherichia coli, Enterococcus hirae, Pseudomonas aeruginosa, Candida albicans and the Spores of Aspergillus brasiliensis.</i>	
APPLICATION	For general cleaning purpose of all synthetic materials, hard surfaces, aluminium and fabrics. Excellent for use after assembly of painted parts that need cleaning from handling and assembly stains.	
OPTIMAL WORKING	Temperature	15-35°C (60-95°F)
CONDITIONS	Relative humidity	10-80%
PRECAUTIONS	Use rubber gloves. See SDS for further detailed information.	
DENSITY	1.0 kg/L	8.3 lb. /gal.
PACKAGING	5L	
STORAGE STABILITY	In closed containers and at T=5-25°C (41-77°F): 1 year. !! Protect from sun light!!	

WWW.HSH-AERO.COM

The information contained in this document is given in good faith by HSH and based on HSH current knowledge. It is only an indication and is in no way binding particularly as regards infringement or prejudice to third parties through the use of our products. The information must on no account be used as a substitute for necessary prior tests which alone can ensure that a product is suitable for a given use.