



INTERCOACH 5025

DESCRIPTION	Water rinsable, non-crazing cleaner for use within the interior. INTERCOACH 5025 has been formulated to remove graffiti from plastics, metals and painted substrates. Can also be used as a general purpose cleaner.	
SPECIFICATION	AMS 15/50 approved.	
APPLICATION	For degreasing purpose in case of removal of persistent dirt or stains use INTERCOACH 5025 not diluted. For cleaning painted surface a 50-50 mix with water will give good results. INTERCOACH 5025 may be diluted up to 10 times its volume with water. INTERCOACH 5025 is a high performance cleaner and will in most cases replace hazardous aromatic hydrocarbon or trichloroethylene cleaners.	
OPTIMAL WORKING CONDITIONS	Temperature	15-35°C (60-95°F)
	Relative humidity	10-80%
PRECAUTIONS	Use rubber gloves. See SDS for further detailed information.	
DENSITY	1.0 kg/L	8.3 lb. /gal.
PACKAGING	5L	
STORAGE STABILITY	In closed containers and at T=5-25°C (41-77°F); 5 years.	

WWW.HSH-RAIL.COM

The information contained in this document is given in good faith by HSH and based on HSH current knowledge. It is only an indication and is in no way binding particularly as regards infringement or prejudice to third parties through the use of our products. The information must on no account be used as a substitute for necessary prior tests which alone can ensure that a product is suitable for a given use.