



## INTERCOACH 5035

### DESCRIPTION

A non-poisonous, non-flammable and biodegradable product for interior and exterior cleaning. The use of INTERCOACH 5035 is easy and results in a clean and grease free surface perfect for painting.

### SPECIFICATIONS

/

### APPLICATION

#### EXTERIOR CLEANING

-1 To assure a good cleaning process prior to spraying with INTERCOACH 5035, cool the surface with water when the substrate temperature is higher than 30°C (86°F).

-2 Use product as received (deep cleaning) or diluted to 40% with water (for future cleaning operations).

Note: after 1-2 deep cleaning actions INTERCOACH 5035 will form an anti-static layer, implying that dirt has more difficulty to stick on the surface. Consequently, further cleaning can be done with the 40% dilution product.

-3 Remove heavy contaminants of dried hydraulic fluid deposits with approved spot cleaner.

-4 Spray as fine as possible droplets of INTERCOACH 5035 on the surface to facilitate penetration into the dirt.

- Always work on limited areas to avoid the product drying too quickly.
- Keep the spray nozzle 12-18 inches away from the aircraft or closer in case of windy conditions.

-5 Apply from the bottom to the top to avoid striping.

-6 Use an approved brush to scrub the surface.

-7 Let it work for 30 seconds to 1 minute, allow longer times (3-5 minutes) for heavier deposits.

-8 Rinse with fresh water.

#### INTERIOR CLEANING

- **Ceilings, tables, plastics side walls, toilets: use 40% diluted product.**
- **Leather seats: use 20-40% diluted product (\*).**

- **Carpets: use 10-20% diluted product (\*).**  
 (\*) conduct a performance test before deciding to use the product on these surfaces.

-1 Spray a thin layer of INTERCOACH 5035 on the substrate or apply the product with a wetted cloth.

-2 Brush in with a soft haired brush to facilitate the action of the product (+/- 15 seconds).

-3 Remove the product and contaminants with a damp sponge.

-4 Retreat again if necessary.

-5 Rinse with water or damp sponge.

-6 If necessary, dry the surface with a clean towel.

## **PRECAUTIONS**

Use rubber gloves.  
 See SDS for further detailed information.

## **DENSITY**

1.0 kg/L 8.3 lb. /gal.

## **PACKAGING**

5 L

## **STORAGE STABILITY**

In closed containers and at T=5-25°C (41-77°F): 5 year.

## **WWW.HSH-RAIL.COM**

The information contained in this document is given in good faith by HSH and based on HSH current knowledge. It is only an indication and is in no way binding particularly as regards infringement or prejudice to third parties through the use of our products. The information must on no account be used as a substitute for necessary prior tests which alone can ensure that a product is suitable for a given use.