



INTERCOACH 5551

DESCRIPTION	Degreaser replacing 1,1,1-trichlorethane and has identical physical properties combined with environmental safety.	
SPECIFICATIONS	/	
APPLICATION	<p>INTERCOACH 5551 performs extremely well in special cleaning techniques like degreasing optical precision instrument parts and electrical components.</p> <p>INTERCOACH 5551 is a non-flammable solvent exempt of chlorine or fluorine. Can be used in vapor degreasing installations, in ultrasonic degreasing or for cold manual cleaning of complex parts.</p> <p>No rinsing or extra degreasing is necessary since no measurable residues are found on the cleaned surface.</p>	
DENSITY	1.33 kg/L	11.1 lb. /gal.
PRECAUTIONS	Use Viton gloves (prolonged contact) or nitrile gloves (short contact). See SDS for further detailed information.	
PACKAGING	1L 5L	
STORAGE STABILITY	In closed containers and at T=5-25°C (41-77°F); 2 years.	

WWW.HSH-RAIL.COM

The information contained in this document is given in good faith by HSH and based on HSH current knowledge. It is only an indication and is in no way binding particularly as regards infringement or prejudice to third parties through the use of our products. The information must on no account be used as a substitute for necessary prior tests which alone can ensure that a product is suitable for a given use.